
# Data sheet


## M12 Bus-/Railcat Patch cord, D-coded, 2.0 m, RJ45 plug - RJ45 plug, BETAtrans®

**P/N 142MPD55020**
**EAN 4251394664415**
2026/10/06
Version: F


## Illustrations



Dimensional drawing




Wiring diagram




See enlarged drawings at the end of document

## Product specification

Halogen-free, electron beam crosslinked Cat.5 data wire with improved behavior under fire conditions and increased temperature resistance. This wire is used in fixed and protected installation in railway vehicles and buses and meets the fire protection requirement according to EN 45545-2 (HL1 - HL3). It is optimally suited for applications of class D (ECN and ETB) according to IEEE 802.3. For installation, the notes according to EN 50355 and EN 50343 must be observed. Because of the thin wall thickness, this wire is especially useful for connecting the overmolded RJ45 connectors. BETAtrans® is a registered trademark of LEONI Studer AG, Switzerland. Special properties: flame retardant, LABS free, RoHs compliant, halogen free, increased thermal load capacity, low smoke emission, oil and fuel resistant, UN ECE-R 118.01 Fire protection: DIN EN 45545-2 HL1-3, DIN 5510 fire protection levels 1-4, NF F16-101 category A1, A2, B, UNI CEI 11170, danger level LR1-LR4, UN ECE-R 118.01

- Standard variants: 1.0 m, 2.0 m, 5.0 m, 10.0 m.
- Other cable lengths on request.

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

# M12 Bus-/Railcat Patch cord, D-coded, 2.0 m, RJ45 plug - RJ45 plug, BETAtrans®

P/N 142MPD55020
EAN 4251394664415
2026/10/06
Version: F

## Technical Data

### General Data

| | |
|---|---|
| Fields of application | Railway vehicle<br>Buses |
| Applications | Train Communication Network: ETB– Ethernet Train Backbone |
| Design | patch cord |
| Cable length (m) | 2 m |
| Cable length (ft) | 6.56 ft |
| Cable | |
| Cable Type | S/FTP |
| Wiring | Profinet |
| Wire color | yellow, white, orange, blue |
| Color - cable jacket | blue |
| Transmission properties | Cat.5 |
| Connection 1 | |
| Shielding | shielded |
| Dimension (L x W) | 45.5 mm x 13.8 mm |
| Dimension (L x W) | 1.791 in. x 0.543 in. |
| Connection 2 | |
| Dimension (L x W) | 45.5 mm x 13.8 mm |
| Dimension (L x W) | 1.791 in. x 0.543 in. |

### Connections/interfaces

| | |
|---|---|
| Cable | |
| Conductor cross section AWG | AWG 22 |
| Conductor diameter (mm) | 0.75 m |
| Conductor diameter (inch) | 0.03 in. |
| Cable construction | 1x4 |
| Stranded wire structure | 7x0.25mm |
| Outer diameter cable jacket (mm) | 6.6 mm |
| Outer diameter cable jacket (inch) | 0.26 in. |
| Connection 1 | |
| Connector type | RJ45 plug |
| Coding | Industrial |
| Type of plug contact, field side | Male (plug) |

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

# M12 Bus-/Railcat Patch cord, D-coded, 2.0 m, RJ45 plug - RJ45 plug, BETAtrans®

P/N 142MPD55020
EAN 4251394664415
2026/10/06
Version: F

## Technical Data

| | |
|---|---|
| **Connections/interfaces** | |
| Connection 1 | |
| Cable feed arrangement, field side | straight |
| Number of poles | 4 |
| Pin Assignment | 1YE, 2OG, 3 WH , 6 BU |
| Latching lever protection | yes |
| Color of the cable boot | black |
| Connection 2 | |
| Connector type | RJ45 plug |
| Coding | Industrial |
| Type of plug contact, field side | Male (plug) |
| Cable feed arrangement, field side | straight |
| Number of poles | 4 |
| Pin Assignment | 1YE, 2OG, 3 WH , 6 BU |
| Latching lever protection | yes |
| Color of the cable boot | black |
| **Electrical characteristics** | |
| Connection 1 | |
| Current carrying capacity per pin (at 40 °C) | 1 A |
| Connection 2 | |
| Current carrying capacity per pin (at 40 °C) | 1 A |
| **Mechanical data** | |
| Cable | |
| Bending radius (fixed) | 6 x Ø cable |
| Connection 1 | |
| Mechanical life | min. 750 mating cycles |
| Connection 2 | |
| Mechanical life | min. 750 mating cycles |

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

# M12 Bus-/Railcat Patch cord, D-coded, 2.0 m, RJ45 plug - RJ45 plug, BETAtrans®

P/N 142MPD55020
EAN 4251394664415
2026/10/06
Version: F

## Technical Data

### Materials and material properties

| | |
|---|---|
| Cable | |
| Material - Cable jacket | BETAtrans® Polyolefin Copolymer |
| Material - Wire insulation | BETAtrans® Cell PE |
| Flame retardancy | yes, according to IEC 60332-1-2 |
| Connection 1 | |
| Material - Contact | CuZnPb (brass) |
| Material - Contact surface | Au (gold) |
| Material - Contact carrier | Plastics, TPE, BK |
| Material - Shielded housing | Metal, CuZn, nickel-plated |
| Connection 2 | |
| Material - Contact | CuZnPb (brass) |
| Material - Contact surface | Au (gold) |
| Material - Contact carrier | Plastics, TPE, BK |
| Material - Shielded housing | Metal, CuZn, nickel-plated |
| RoHS | compliant |

### Environmental conditions

| | |
|---|---|
| Cable | |
| Temperature range (fixed) | -40 °C - max. 85 °C |
| Temperature range (fixed) | -40 °F - 185 °F |
| Connection 1 | |
| | -40 °C |
| | -40 °F |
| Protection category (mounted) | IP20 |
| Connection 2 | |
| Protection category (mounted) | IP20 |
| Operating temperature classes | OT1 - OT4 |
| Operating temperature range | -40 to 70 |

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

# M12 Bus-/Railcat Patch cord, D-coded, 2.0 m, RJ45 plug - RJ45 plug, BETAtrans®

P/N 142MPD55020
EAN 4251394664415
2026/10/06
Version: F

## Technical Data

| Standards/Regulations | |
|---|---|
| General requirements | ISO/IEC 11801-1 \| DIN EN 50173-1 |
| Cable | |
| Buses - Fire safety | UN ECE-R 118.01 |
| Connection 1 | |
| Free and fixed connectors | IEC 60603-7-5:2011 |
| Shock and vibration | Class 1, category B (DIN EN 61373) |
| Connection 2 | |
| Free and fixed connectors | IEC 60603-7-5:2011 |
| Shock and vibration | Class 1, category B (DIN EN 61373) |
| Contact holder | Thermoplastic |
| Sealings | Elastomer |
| Shock and vibration | EN 50155:2021, EN 61373:2010 Class 1 Category B |
| Salt spray | EN 50155:2021, (DIN EN 60068-2-11:2000-02/ 48-hour KA test) |

| Classifications | |
|---|---|
| ETIM 8.0 | EC002599 |
| ETIM 9.0 | EC002599 |
| ETIM 10.0 | EC002599 |

| Packing details | |
|---|---|
| Type of packaging | 1 pc(s) / plastic bag |

### Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

# M12 Bus-/Railcat Patch cord, D-coded, 2.0 m, RJ45 plug - RJ45 plug, BETAtrans®

**P/N 142MPD55020**
**EAN 4251394664415**
2026/10/06
Version: F

## Accessories

| P/N | Designation |
|---|---|
| MMF881A115 | M12 jack, D-coded, IP67, Cat.5, Ø 6-9.7 mm, field assembly, straight |
| MNF881A115 | M12 plug, D-coded, IP67, Cat.5, Ø 6-9.7 mm, field assembly, straight |
| MWN811A115 | M12 Panel feed through adapters, D-coded, to RJ45 - straight |


© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

# M12 Bus-/Railcat Patch cord, D-coded, 2.0 m, RJ45 plug - RJ45 plug, BETAtrans®


P/N 142MPD55020
EAN 4251394664415
2026/10/06
Version: F

## Illustrations

Dimensional drawing




Wiring diagram





© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

# M12 Bus-/Railcat Patch cord, D-coded, 2.0 m, RJ45 plug - RJ45 plug, BETAtrans®

**P/N 142MPD55020**
**EAN 4251394664415**
2026/10/06
Version: F

## Illustrations

Principle diagram



METZ CONNECT GmbH | Im Tal 2 | 78176 Blumberg | Germany
Phone +49 7702 533-0 | Fax +49 7702 533-433 | info@metz-connect.com
Weitere Dokumentation siehe / additional documentation see / documentation supplémentaire voir www.metz-connect.com

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!