

# Data sheet

## OpDAT REG K Prefab 4xSC-D OS2

Page 1/5

P/N

15024K0E204-E

EAN 4251394671079


2025/07/23

Version: C

### Illustrations



Dimensional drawing



See enlarged drawings at the end of document

### Product specification

- very compact patch distributor for TH35 mounting rail
- prepared for the installation of pre-assembled installation cables (OpDAT Prefab)
- equipped with 4 SC-D adapters
- different mounting variants on the mounting rail are possible
- cable feed from above or below
- cable entry M20 included in delivery
- housing (W x H x D): 50 x 85 x 130 mm



# OpDAT REG K Prefab 4xSC-D OS2

P/N  
15024K0E204-E  
EAN 4251394671079  
2025/07/23  
Version: C

## Technical Data

### General Data

Fields of application	structured building cabling office areas data center
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	Splice distributor
Mounting style	Standard rail TH35
Transmission technology	Fiber optic
Color	gray
Dimensions	
Dimension (L x W x H)	145.3 mm x 139 mm x 50 mm
Dimension (L x W x H)	5.72 in. x 5.472 in. x 1.969 in.
Fiber class	OS2
Mode type of the fiber	Singlemode
Shape	UPC (Ultra Physical Contact)

### Connections/interfaces

Connector technology interface 1	SC-D Couplers
Connector technology interface 2	SC-D Couplers
Number of ports interface 1	4
Number of ports interface 2	4
Number of equipped ports interface 1	4
Number of ports interface 2 equipped	4
Number of ports with dust protection interface 1	4
Number of ports with dust protection interface 2	4
Cable access/outlet	from top or bottom

### Mechanical data

Cut-out	SC-D, LC-Q, ST-D
Connector type	duplex
Life - Number of mating cycles	min. 500
strain relief	M gland

**OpDAT REG K Prefab 4xSC-D OS2**

P/N

15024K0E204-E

EAN 4251394671079

2025/07/23

Version: C

**Technical Data****Materials and material properties**

Material - Housing	sheet steel
Material - Housing finish	powder-coated
Material - Sleeve	ceramic, slotted
Material - Coupler housing	GD-Zn
Halogen free	yes
RoHS	compliant

**Classifications**

ETIM 7.0	EC001130
ETIM 8.0	EC001130
ETIM 9.0	EC001130
ETIM 10.0	EC001130

**Packing details**

Type of packaging	1 pc(s) / plastic bag
-------------------	-----------------------

**Application note**

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).



Data sheet  
OpDAT REG K Prefab 4xSC-D OS2

Page 4/5

P/N  
15024K0E204-E  
EAN 4251394671079  
2025/07/23  
Version: C

## Accessories

P/N	Designation
150240M20Z-E	OpDAT strain relief M20

Data sheet

OpDAT REG K Prefab 4xSC-D OS2

Page 5/5

P/N

15024K0E204-E

EAN 4251394671079

2025/07/23

Version: C

## Illustrations

Dimensional drawing

