

Data sheet

PC board jack M12, X-coded, 8-pole, IP67,
90° angled, max. 4 mm wall thickness


Page 1/7

P/N
MMT471A315-0001
EAN 4250184169482
2026/05/20
Version: R


Illustrations



Dimensional drawing



Drill pattern



See enlarged drawings at the end of document

Product specification

- PC board jack M12
- 8-pole, X-coded according to IEC 61076-2-109
- 90° angled
- 10 GBit suitable according to IEEE 802.3an
- THR solderable
- Side entry
- Contact carriers green
- IP67 when plugged in
- suitable for a wall thickness up to 4 mm
- suitable for applications in the railway industry according to data sheet



Data sheet

**PC board jack M12, X-coded, 8-pole, IP67,
90° angled, max. 4 mm wall thickness**

P/N
MMT471A315-0001
EAN 4250184169482
2026/05/20
Version: R

Technical Data

General Data

Dimensions	
Dimension (L x W x H)	30.65 mm x 16.82 mm x 18.95 mm
Dimension (L x W x H)	1.207 in. x 0.662 in. x 0.746 in.
Jack	M12
Coding	X-coded
For wall thickness (mm)	4 mm
For wall thickness (inch)	0.157 in.

Electrical characteristics

Rated voltage	50 V AC / 60 V DC
Effective value of the withstand voltage	0.5 kV
Nominal current at 50 °C	max. 0.5 A
Insulation resistance	min. 100 MOhm
Overvoltage category	II
Degree of pollution	2

Mechanical data

Material	
Material - Housing	CuZnPb
Material - Contact	CuZnPb
Contact surface	Ni + Au
Life - Number of mating cycles	>= 100
Tightening torque - Plug	0,6 - 1 Nm
Tightening torque - Jack mounting	3 Nm +/- 0,5 Nm (see illustration at the end of the data sheet)
Protection category	IP67 when plugged in

Climatic properties

Temperature - Operating °C	-40 °C - 85 °C
Temperature - Operating °F	-40 °F - 185 °F

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

Data sheet

Page 3/7

**PC board jack M12, X-coded, 8-pole, IP67,
90° angled, max. 4 mm wall thickness**

P/N
MMT471A315-0001
EAN 4250184169482
2026/05/20
Version: R

Technical Data

Approvals	
Approval mark UL/CSA	E178484
Packaging	
Type of packaging	10 pc(s) / blister packaging
Standards/Regulations	
Railway applications	
Insulating body	PA UL 94 V0 complies with HL1-HL3; R26 according to EN 45545-2:2020+A1:2023
Flammable mass (g)	0.62 g
Sealings	Elastomer
Flammable mass (g)	0.17 g
Salt spray	DIN EN 50155:2018-05, (DIN EN 60068-2-11:2000-02/ 48h test KA)
Shock and vibration	DIN EN 50155:2018-05, DIN EN 61373:2011-04 Class 1 Category B
Classifications	
ETIM 7.0	EC002637
ETIM 8.0	EC002637
ETIM 9.0	EC002637
ETIM 10.0	EC002637

Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way. At METZ CONNECT's request, the Customer shall submit and make available meaningful evidence (e.g. test and laboratory protocols, certifications, etc.).

Data sheet

Page 4/7

**PC board jack M12, X-coded, 8-pole, IP67,
90° angled, max. 4 mm wall thickness**

P/N

MMT471A315-0001

EAN 4250184169482

2026/05/20

Version: R

Accessories

P/N	Designation
700701	M12 screw plug for jacks IP54



Data sheet


Page 5/7

**PC board jack M12, X-coded, 8-pole, IP67,
90° angled, max. 4 mm wall thickness**


P/N
MMT471A315-0001
EAN 4250184169482
2026/05/20
Version: R

Illustrations

Dimensional drawing



Drill pattern



Data sheet

Page 6/7

**PC board jack M12, X-coded, 8-pole, IP67,
90° angled, max. 4 mm wall thickness**

P/N

MMT471A315-0001


EAN 4250184169482

2026/05/20

Version: R

Illustrations

Cut-out



Data sheet

Page 7/7

**PC board jack M12, X-coded, 8-pole, IP67,
90° angled, max. 4 mm wall thickness**

P/N

MMT471A315-0001


EAN 4250184169482

2026/05/20

Version: R

Illustrations

Mounting instruction



Tightening torque - Jack mounting

3 Nm +/- 0,5 Nm (Measured between tightening nut and housing nut)

