# Data sheet
## ST25503HBNN, 3-pole



**P/N**
**ST25503HBNN**

2026/11/23
Version: H

## Illustrations



Dimensional drawing as an example



Drill pattern as an example



See enlarged drawings at the end of document

## Product specification

- spring clamp terminal block, THT solderable
- centerline 5.00 mm, direction of connection 90°
- fittable without loss of poles
- color black

METZ CONNECT GmbH | Im Tal 2 | 78176 Blumberg | Germany
Phone +49 7702 533-0 | Fax +49 7702 533-433 | info@metz-connect.com
Weitere Dokumentation siehe / additional documentation see /
documentation supplémentaire voir www.metz-connect.com

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

## Technical Data

| | | | |
|---|---|---|---|
| **General Data** | | | |
| Solder pin length | 2.6 mm | | |
| pole size | 3 | | |
| Insulating material class | CTI 600 | | |
| clearance/creepage dist. | 4 mm | | |
| Protection category | IP20 | | |
| Insul. strip length | 8 mm | | |
| Rated current | 19 A | | |
| Overvoltage category | III | III | II |
| Pollution degree | 3 | 2 | 2 |
| Rated voltage | 320 V | 800 V | 800 V |
| Rated test voltage | 6 kV | 6 kV | 6 kV |
| **Terminal data** | | | |
| rat.wiring solid AWGmax | 0.2 mm² - 2.5 mm² / AWG 24 - AWG 14 | | |
| rat.wiring strand.AWGmax | 0.2 mm² - 2.5 mm² / AWG 24 - AWG 12 | | |
| **Approvals** | | | |
| V / A / AWG | 300 / 17 / 24 - 12 | | |
| approval UL - File No. | E121004 | | |
| | 250 V / 2.5 kV / 19 A | | |
| **Material** | | | |
| insulating material | PA66/PPA | | |
| flammability class | V0 | | |
| spring material | Spring steel | | |
| contact material | CuSn | | |
| Contact surface | Sn | | |
| **Climatic Data** | | | |
| upper limit temperature | 105 °C | | |
| lower limit temperature | -40 °C | | |
| **general** | | | |
| Tolerance | ISO 2768 -mH | | |
| Solderability | Acc. to JEDEC JESD22-B102E 245°C/5s | | |

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

## Technical Data

### Application note

This product is a standard product of METZ CONNECT. METZ CONNECT is not aware of the specific intended use of the goods by the Customer or any customers of the Customer. The Customer guarantees that it has fully and sufficiently tested the use of the goods and any product modifications, product changes or product enhancements with regard to the specific intended use in accordance with the state of the art or in any other way.

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

## Illustrations

Dimensional drawing as an example



L=(pole size - 1) x centerline + 5 mm [0.197]

© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!

## Illustrations

Drill pattern as an example



© 2026 METZ CONNECT - Technische Änderungen vorbehalten! Subject to modifications! Sous réserve de modifications techniques!